

# PENTECH INC. Model-VS3MM

Conforms to CID A-A-59982

**Fast and Uniform Spray Application of  
MIL-PRF-24667 Type-IV & Type-X Non Skid Deck Coatings**  
**Quick Assembly – Easy Operation – Rapid Clean Up**



27" L x 22" W x 20" H

Weight: 93 Lbs.

Air Powered, 125 PSI, 70-90 CFM

Max. Hose Length: 25 Ft.

Funnel Capacity: 6 Gallons



- Application rate: 1,200 - 1,300 sq.ft. / Hour
  - Average coverage / gallon: 60 sq.ft.
  - Spray is 50 % faster than roll application
  - Sprays all MIL-PRF 24667 Type-IV non skid coatings.
- On-board air /water coalescer  
No hose or gun clogging issues.  
Does not require electricity  
No pressure in hose when not spraying  
Adjustable material flow  
Adjustable atomizing air flow  
Small, light weight, and maneuverable to access hard to reach areas  
Tool kit included

**USS Mahan  
DDG-72  
NCP Coatings N-9020  
Polysiloxane Non-Skid  
(Photo Courtesy of NRL)**

**Developed in collaboration with the  
Naval Research Laboratory**

**PENTECH, INC.**

POC: Tom Pennell  
941-739-2700 Ext. 303  
tpennell@Pentech.us  
www.pentech.us